## **EUROPEAN PATENT OFFICE**

## Patent Abstracts of Japan

PUBLICATION NUMBER

58142060

PUBLICATION DATE

23-08-83

APPLICATION DATE

15-02-82

APPLICATION NUMBER

57022454

APPLICANT: HONDA MOTOR COLTD;

INVENTOR: OTOSHI YASUSHI;

INT.CL.


: F16H 9/18

TITLE

TORQUE DETECTING CAM

MECHANISM OF AUTOMATIC BELT

SPEED CHANGE DEVICE



ABSTRACT: PURPOSE: To obtain the belt lateral pressure of a driven pulley matching with required speed change characteristic by changing the operation angle of a cam groove of a driven cam in relation to a roller pin to the extent from two steps up to the stepless condition.

> CONSTITUTION: If an operation angle of a cam groove 5g in relation to a roller pin 5f is set to  $\theta(=45^{\circ})$  in a low-speed and high torque driving area and  $\theta_1(<\theta)$  on the way to high-speed and low torque driving area, the belt lateral pressure Q<sub>2</sub> which works on a driven pulley 5 in low-speed and high torque driving area at this time is made larger than belt lateral pressure Q'2 in the high-speed and low torque driving area. Further, since the driving force of the driven pulley 5 becomes smaller than that of a linear cam groove when the engine speed reaches the definite number of revolution, automatic speed change of the pulley from the low-speed and high torque area to the high-speed and low torque area becomes easy and load of the engine is decreased, therefore, the car speed is increased in spite of a decrease in the number of engine revolution.

COPYRIGHT: (C)1983,JPO&Japio